

## INK TOP ORESSER













## RINK TOP DRESSER 1210

The 1210 is a trailed unit for use behind any prime mover. The four pivoting wheels ensure equal and low ground pressure, even on undulating ground. It is hydraulically powered, either from the prime mover or optional auxiliary tank and pump unit.

The full width continuous loop belt has edge guides to ensure central tracking. The Rink delivery and metering system is designed to ensure smooth, even distribution of all types of top dressing materials, including wet sand. The 12 series dressers are ideal for all golf course applications. The hopper is made of aluminum to avoid rusting.



WORKING SPECIFICATIONS	Length	96 in (2.40 m)
	Road Width	81 in (2.03 m)
	Height	44 in (1.10 m)
	Loading Capacity	1.3 cu yd (1.0 cu m)
	Spreading Width	72 in (1.80 m) / Up to 30 ft (9 m) With Optional Spinners
	Tire Equipment	4 Swing tires Trelleborg Garden Slick 18 x 9.50 - 8
	Tire Pressure	15 psi (1.0 bar)
	Speed Limit	19 mph (30 km/h)
	Towing Capacity	min 15 HP (20 Kw)
	Spreading Amount	Continuously adjustable
	Minimum Conveying Capacity Towing Vehicle	3.6 US gal/min (15 l/min)
	Hydraulics Required	3.6 gpm/980 psi, 4.6 gpm with spinners

FEATURE	BENEFIT
Precise metering	Enables fine control over density
Easy belt adjustment	Two tracking guides keep belt centered
Exact spreading widths	For neat and economical operation
Ideal weight distribution	Prevents compaction and damage to turf
	Precise metering  Easy belt adjustment  Exact spreading widths

## CALL FOR YOUR FREE DEMO TODAY!

S

Our commitment is to fully satisfy the needs of our customer. For immediate assistance, contact your local distributor or our Sales & Marketing Office at 636-326-1009.



Redexim North America Inc. 29 Cassens Court Fenton, MO 63026, USA Tel: 636-326-1009 Fax: 636-326-4884 www.redexim.com E-mail: redexim@aol.com